

Name: _____

NetID: _____ Lecture: A B

Discussion: Thursday Friday 9 10 11 12 1 2 3 4 5 6

(15 points) Check the (single) box that best characterizes each item.

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = T(n-1) + n$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

$T(1) = d$	$\Theta(\log n)$	☐	$\Theta(\sqrt{n})$	☐	$\Theta(n)$	☐	$\Theta(n \log n)$	☐
$T(n) = 2T(n/4) + n$	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

The running time of mergesort is $O(n^3)$. true ☐ false ☐

For a problem to satisfy the definition of NP, a
 “no” answer must have a succinct justification. true ☐ false ☐

The Travelling Salesman Problem polynomial ☐ exponential ☐ in NP ☐

Name: _____

NetID: _____ Lecture: A B

Discussion: Thursday Friday 9 10 11 12 1 2 3 4 5 6

(15 points) Check the (single) box that best characterizes each item.

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = 2T(n/2) + n$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = 3T(n-1) + c$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

Algorithm A takes n^5 time. On one input, A takes x time. How long will it take if I double the input size?

$2x$ ☐ $5x$ ☐ $32x$ ☐ x^5 ☐

The Marker Making problem can be solved in polynomial time.

true ☐ false ☐ not known ☐

Problems in class P (as in P vs. NP) require exponential time

true ☐ false ☐ not known ☐

Name: _____

NetID: _____

Lecture: A B

Discussion: Thursday Friday 9 10 11 12 1 2 3 4 5 6

(15 points) Check the (single) box that best characterizes each item.

$T(1) = d$	$\Theta(\log n)$	☐	$\Theta(\sqrt{n})$	☐	$\Theta(n)$	☐	$\Theta(n \log n)$	☐
$T(n) = T(n/2) + d$	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = 3T(n/3) + n$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

All ways to assign True/False values to n input variables	$\Theta(\log n)$	☐	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐
	$\Theta(n^3)$	☐	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐

Producing all parses for a sentence.	polynomial	☐	exponential	☐	in NP	☐
---	------------	--------------------------	-------------	--------------------------	-------	--------------------------

The chromatic number of a graph with n nodes can be found in polynomial time.	true	☐	false	☐	not known	☐
--	------	--------------------------	-------	--------------------------	-----------	--------------------------

Name: _____

NetID: _____ Lecture: A B

Discussion: Thursday Friday 9 10 11 12 1 2 3 4 5 6

(15 points) Check the (single) box that best characterizes each item.

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = 3T(n/2) + n$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

$T(1) = d$	$\Theta(\log n)$	☐	$\Theta(\sqrt{n})$	☐	$\Theta(n)$	☐	$\Theta(n \log n)$	☐
$T(n) = T(n-1) + c$	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

The running time of the Towers of Hanoi solver is $\Theta(n!)$

true ☐ false ☐

Circuit satisfiability can be solved in exponential time.

true ☐ false ☐ not known ☐

Producing all parses for a sentence requires exponential time.

true ☐ false ☐ not known ☐

Name: _____

NetID: _____ Lecture: A B

Discussion: Thursday Friday 9 10 11 12 1 2 3 4 5 6

(15 points) Check the (single) box that best characterizes each item.

$T(1) = d$	$\Theta(\log n)$	☐	$\Theta(\sqrt{n})$	☐	$\Theta(n)$	☐	$\Theta(n \log n)$	☐
$T(n) = T(n/2) + n$	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = 2T(n/3) + d$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

Algorithm A takes 2^n time. On one input, A takes x time. How long will it take if I add one to the input size?

$x + 2$	☐	$2x$	☐	2^x	☐	x^2	☐
---------	--------------------------	------	--------------------------	-------	--------------------------	-------	--------------------------

Problems in class P (as in P vs. NP) can be solved in exponential time

true	☐	false	☐	not known	☐
------	--------------------------	-------	--------------------------	-----------	--------------------------

Deciding if a graph is 2-colorable

polynomial	☐	exponential	☐	in NP	☐
------------	--------------------------	-------------	--------------------------	-------	--------------------------

Name: _____

NetID: _____ Lecture: A B

Discussion: Thursday Friday 9 10 11 12 1 2 3 4 5 6

(6 points) Your partner has implemented the function Merge(A,B), which merges two sorted linked lists of integers. Using Merge, fill in the missing parts of this implementation of Mergesort.

Mergesort($L = (a_1, a_2, \dots, a_n)$) \\ input is a linked list L containing n integers

p = floor(n/2)

(9 points) Check the (single) box that best characterizes each item.

$T(1) = d$	$\Theta(n)$	☐	$\Theta(n \log n)$	☐	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐
$T(n) = 3T(n/2) + d$	$\Theta(n^{\log_3 2})$	☐	$\Theta(n^{\log_2 3})$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

Merging two sorted lists	$\Theta(1)$	☐	$\Theta(\log n)$	☐	$\Theta(n)$	☐	$\Theta(n \log n)$	☐
	$\Theta(n^2)$	☐	$\Theta(n^3)$	☐	$\Theta(2^n)$	☐	$\Theta(3^n)$	☐

Circuit satisfiability can be solved in polynomial time.

true ☐ false ☐ not known ☐